

Durham Research Online

Deposited in DRO:

24 July 2018

Version of attached file:

Accepted Version

Peer-review status of attached file:

Peer-reviewed

Citation for published item:

Koulieris, G.A. and Drettakis, G. and Cunningham, D. and Mania, K. (2016) 'Gaze prediction using machine learning for dynamic stereo manipulation in games.', in 2016 IEEE Virtual Reality Conference (VR) : Greenville, South Carolina, USA, 19-23 March 2016. Proceedings. Piscataway, NJ: IEEE, pp. 113-120.

Further information on publisher's website:

<https://doi.org/10.1109/vr.2016.7504694>

Publisher's copyright statement:

© 2016 IEEE. Personal use of this material is permitted. Permission from IEEE must be obtained for all other uses, in any current or future media, including reprinting/republishing this material for advertising or promotional purposes, creating new collective works, for resale or redistribution to servers or lists, or reuse of any copyrighted component of this work in other works.

Additional information:

Use policy

The full-text may be used and/or reproduced, and given to third parties in any format or medium, without prior permission or charge, for personal research or study, educational, or not-for-profit purposes provided that:

- a full bibliographic reference is made to the original source
- a [link](#) is made to the metadata record in DRO
- the full-text is not changed in any way

The full-text must not be sold in any format or medium without the formal permission of the copyright holders.

Please consult the [full DRO policy](#) for further details.

Supplemental material: Gaze Prediction using Machine Learning for Dynamic Stereo Manipulation in Games

George Alex Koulieris*
Technical University of Crete
INRIA

George Drettakis†
INRIA

Douglas Cunningham†
Technical University of Cottbus

Katerina Mania[§]
Technical University of Crete

1 INTRODUCTION

This supplemental document provides details on the various steps of our approach. Most of these are heavily based on standard methodology in the literature, but some adaptation was required to our specific problem.

2 EYE TRACKING DATA DE-PROJECTION

The eye tracker yields time-coded $[x,y]$ coordinates of fixations in the $[0,1]$ range. To identify which object was fixated in the game FoV, we de-projected the eye-gaze space $[x,y]$ coordinates in the frustum of the participant’s dominant eye. A ray was then reconstructed originating from the dominant eye camera center and passing through the de-projected eye coordinates. The ray was advanced through the scene. The first non-transparent 3D model bounding volume that the ray hit, was considered the attended object.

3 STEREO GRADING DETAILS

We use the standard asymmetric viewing frusta, as presented among others [4] shown in Fig. 1.




Figure 1: Asymmetric frustum stereo geometry.

In our system following the barycenter estimation of an object or a group of objects, the distance C is estimated as the barycenter + a user selected parameter that signifies how protruding or submerged the object/object will be perceived in relation to the zero parallax plane, i.e. the virtual screen. Distance D_{eye} is a user-defined seed value for our dynamic disparity control method.

To generate an asymmetric viewing frustum the near clipping plane's top, bottom, left and right coordinates in addition to the near

*galekoul@gmail.com

[†]george.drettakis@inria.fr

[‡]cunningh@tu-cottbus.de

§k.mania@ced.tuc.gr

and far clipping planes distances are required [3]. For the desired virtual screen a mono-frustum would be *AOB*. For this monoscopic frustum let us denote the Field of View (FOV) angle along the y-axis as θ_{FOV_y} and the aspect ratio of the mono-frustum as r_{aspect} . We then estimate the parameters for both left and right frustums, in addition to D_{eye} as a system of simultaneous linear equations:

$$top = D_{near} \tan \frac{\theta_{FOVy}}{2} \quad \& \quad bottom = -top \quad (1)$$

The left frustum ALB , intersects the near clipping plane at d_{left} distance left of LL' and at d_{right} distance right of LL' . Given the triangles ALL' and BLL' we find that:

$$a = r_{aspect} C \tan \frac{\theta_{FOVy}}{2} \quad \& \quad \frac{d_{left}}{b} = \frac{d_{right}}{c} = \frac{D_{near}}{C} \quad (2)$$

$$b = a - \frac{D_{eye}}{2} \quad \& \quad c = a + \frac{D_{eye}}{2} \quad (3)$$

By interchanging b and c we estimate parameters for the right frustum ARB .

The image disparity p of a vertex with scene distance w is positive when the object is behind the virtual scene, and negative otherwise and is known as parallax. Parallax depends both on interaxial separation D_{eye} and convergence distance C . We estimate a comfortable D_{eye} for a predetermined maximum on-screen parallax $|p|$ (see [2, 1]) based on user-display distance and display size:

$$D'_{eye} = \frac{w|p|}{w-c} \quad (4)$$

For the left eye frustum, parameters are:

$$left = -a + \frac{D'eye * D_{near}}{2C} \quad right = a + \frac{D'eye * D_{near}}{2C} \quad (5)$$

For the right eye frustum, parameters are:

$$left = -a - \frac{D'eye * D_{near}}{2C} \quad right = a - \frac{D'eye * D_{near}}{2C} \quad (6)$$

REFERENCES

- [1] G. R. Jones, D. Lee, N. S. Holliman, and D. Ezra. Controlling perceived depth in stereoscopic images. In *Photonics West 2001-Electronic Imaging*, pages 42–53. International Society for Optics and Photonics, 2001.
- [2] T. Shibata, J. Kim, D. M. Hoffman, and M. S. Banks. The zone of comfort: Predicting visual discomfort with stereo displays. *Journal of vision*, 11(8):11, 2011.
- [3] M. Woo, J. Neider, T. Davis, and D. Shreiner. *OpenGL programming guide: the official guide to learning OpenGL, version 1.2*. Addison-Wesley Longman Publishing Co., Inc., 1999.
- [4] A. J. Woods, T. Docherty, and R. Koch. Image distortions in stereoscopic video systems. In *IS&T/SPIE's Symp. on Electronic Imaging: Science and Technology*, pages 36–48. International Society for Optics and Photonics, 1993.